

Exam : **NS0-175**

Title : Cisco and NetApp FlexPod
Design Specialist

Version : DEMO

1. In addition to what is used in a FlexPod Datacenter design, which new hardware component is required to support Cisco Application Centric Infrastructure (ACI)?

- A. Cisco FEX
- B. Cisco VIC
- C. Cisco Nexus 1110X
- D. Cisco APIC

Answer: D

2. All of the following are supported interface types EXCEPT _____.

- A. ATM
- B. Gigabit Ethernet, copper
- C. 10/100 Ethernet
- D. Gigabit Ethernet, fiber

Answer: A

3. Which one of the following access methods will maintain boot messages across reboots?

- A. SSH
- B. RSH
- C. Telnet
- D. Console

Answer: D

4. A customer with a FlexPod Express solution wants to enable remote access to the NetApp storage component.

In this scenario, which two access methods are recommended? (Choose two.)

- A. Telnet
- B. SAML
- C. SSH
- D. RDP

Answer: AC

5. Which two types of Cisco UCS servers are available to be used with a FlexPod Express deployment? (Choose two.)

- A. Cisco UCS C-Series
- B. Cisco UCS B-Series
- C. Cisco UCS E-Series
- D. Cisco UCS S-Series

Answer: AB